



PRODUCT-DETAILS

XT1C 160 TMD 50-500 3p F F

XT1C 160 TMD 50-500 3p F F



General Information

Extended Product Type	XT1C 160 TMD 50-500 3p F F
Product ID	1SDA067394R1
EAN	8015644695194
Catalog Description	XT1C 160 TMD 50-500 3p F F
Long Description	C.BREAKER TMAX XT1C 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 50-500 A

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2347
Environmental Product Declaration - EPD	9AKK108468A1890 9AKK108468A7793
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 55.9 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Declaration	9AKK108466A1424
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	6963f79e-5b3e-491f-8111-ed51582b95f5 Italy
Simplified SCIP	03623cf1-c0d9-4f9d-a987-0129b1b5c4e3 Germany 0b897293-8966-400d-85d3-3adb67e5645e Netherlands 788f7ce1-ce81-46b1-b516-e8a1a5810a29 Netherlands aa1def39-a5e1-402c-a7fb-1f69c65bf0cf Germany 75a37be3-c5f2-48d2-921c-196f3e715fbb Denmark 2b729765-22b2-414d-96db-c45c85b86b34 Germany 73e3b539-3241-4e7c-b2e3-a271a8580cce Croatia f266fe7c-cd54-450c-984b-762ab9f9b7b5 Czech Republic 01bac839-3a95-4abc-9842-01bf939126de Netherlands 6d189084-7c30-4847-b66c-12452df5457e Netherlands afbc9104-3742-44d7-8a17-ef24c66adf7e Estonia fa14a73d-5be7-45d6-bea7-eef52df9a461 Greece c090809c-f591-4fd0-8f91-3f7005422d41 Portugal 8c6a9e39-4f7d-4d91-a84a-7c5fae9fab39 Bulgaria a751af1f-ba16-4b16-bae1-88bd49a124fd Sweden 189d8f20-fd0b-4ae9-9160-02cedac39911 Poland dfa00889-9143-4640-beda-7b68e77263b4 France e2a75877-0b3c-423d-a60d-9205fd4b7277 Sweden 2ba6904a-b275-40a0-a662-5277d2f0e712 Germany dbbe5839-4af6-41b6-a0d9-d91eb8454cb5 Germany b8b8214a-1d31-430b-aa6b-829d2c2e0845 Spain 30e0bf90-1472-4e80-9b14-b35167a34379 Netherlands 3fc61ee0-7133-460e-943f-e79dba217b6d Poland 5e5400ef-76f0-49e1-9aff-19542ffb47e1 Poland 1bc8a6dc-76f2-4cd5-8b92-6cd0b382a8e5 Finland 46710f5a-a1b8-4e6f-92eb-28c07b84c61b Norway ecb4dd9f-7134-4b06-9ce6-ba53c0aceabe France

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT1CE3050AFF000XXX
E-Number (Finland)	3638609
E-Number (Norway)	4309614
EAN	8015644695194
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth /	70 mm

Length

Product Net Weight	1.1 kg
--------------------	--------

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.12 kg
Package Level 1 EAN	8015644695194

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Technical

Connecting Capacity Main Circuit	Busbar 45.5 ... 80 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 30 ms CB with UVR 30 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 3.7 W
Rated Current (I _n)	50 A
Rated Frequency (f)	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I _i)	500 A
Rated Insulation Voltage (U _i)	800 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 40 kA (230 V AC) 40 kA (240 V AC) 40 kA (380 V AC) 25 kA (415 V AC) 25 kA (440 V AC) 12.5 kA

	(500 V AC) 9 kA (525 V AC) 8 kA (690 V AC) 4 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 3 Poles in Series 25 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 40 kA (230 V AC) 40 kA (240 V AC) 40 kA (380 V AC) 25 kA (415 V AC) 25 kA (440 V AC) 25 kA (500 V AC) 18 kA (525 V AC) 8 kA (690 V AC) 4 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 3 Poles in Series 25 kA
Rated Uninterrupted Current (I _u)	160 A
Rated Voltage (U _r)	690 V
Recommended Screw Driver	Main Circuit M6
Release	TMD
Release Type	TM
Setting Range	35...50 A
Short-Circuit Performance Level	C
Standards	IEC60947-2
Sub-type	XT1
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5532
GL Certificate	1SDL000163R0103
LR Certificate	1SDL000163R0100
UL Certificate	No certification needed
VDE Certificate	No certification needed
Dimension Diagram	1SDH000719R0100
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0001

External Classifications and Standards

ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

eClass

V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

